

SHACMAN

X3000

LORRY TRUCK



Transport type	Complex transport		
Logistics type	Daily industrial products and food		
Distance (km)	≤300km		
Road type	Paved roads		
Drive	6×4	8×4	8×4
Max weight(t)	≤35	≤50	≤50
Crusing speed/Max speed(km/h)	90	90	90
Loaded speed(km/h)	50~65	50~65	50~65
Vehicle model	SX12555R434	SX13155T456	SX13155T456
Engine	WP10.340	WP12.380	WP12.380
Emission standard	Euro II	Euro II	Euro II
Displacement	9.726L	11.596L	11.596L
Rated Output	250kW	280kW	280kW
Max. torque	1350N·m	1500N·m	1500N·m
Transmission	10JSD140	12JSD180T	12JSD180T
Clutch	430	430	430
Frame	850×300 (8+5)	850×300 (8+5)	850×300 (8+5)

Front axle	MAN 7.5T	MAN 7.5T	MAN 7.5T
Rear axle	13T MAN double reduction 4.769	13T MAN double reduction 4.769	13T MAN double reduction 4.769
Tire	12.00R20	12.00R20	12.00R20
Front Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs
Rear Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs
Fuel	Diesel	Diesel	Diesel
Capacity of the fuel tank	400L (Aluminum shell)	400L (Aluminum shell)	400L (Aluminum shell)
Battery	165Ah	165Ah	180Ah
Dimensions(L×W×H)	9575×2490×3450	11425×2490×3450	11425×2490×3450
Trunk(L×W×H)	7500×2300×800	9500×2300×800	9500×2300×800
Wheelbase	4375+1400	1800+4575+1400	1800+4575+1400
After the suspension	2400	2300	2300
Approach / Departure angle (°)	18/12	18/12	18/12
Max.gradeability(%)	34	34	34
Cab	Type	X3000 , mid-lengthened flat roof	
	Equipments	◆ Rear window ◆ Manual sunroof ◆ Hydraulic driver seat with seatbelts ◆ Hydraulic suspension of cab ◆ Electronic air conditioning with temperature control ◆ Electric window ◆ Central locking ◆ Radio with MP3 player	
	Optional	● Air cushioned drivers seat ● Full vehicle WABCO valve ● 11.00R20	